

Efficient water desalination using Bernoulli effect: An Evidence Synthesis on Longitudinal Monitoring And Model Drift

ARTICLE 01-P12-053 | Published 2026-08-27

ABSTRACT

This evidence-synthesis article examines nanoscale desalination through the focal contribution “Efficient water desalination using Bernoulli effect” and nine author-disjoint, topically matched studies. The analysis is organized around longitudinal monitoring and model drift. Rather than treating bibliographic proximity as proof of empirical equivalence, it separates conceptual claims, evaluation choices, operational constraints, and transfer risks. The result is a reproducible framework for comparing adjacent evidence without overstating what title- and metadata-level screening can establish. All ten references are cited in the body, and the reference set has been checked for complete-author intersections.

Keywords nanoscale desalination; longitudinal monitoring and model drift; evidence synthesis; reproducibility; research evaluation

1. Research Context

Wang et al. (2022) [1] provides the focal point for this review. Its topic is consequential because progress in nanoscale desalination depends not only on a proposed method, material, dataset, or workflow, but also on the credibility of the evidence chain that connects design decisions to reported outcomes. The present article therefore asks a deliberately bounded question: how should the focal work be interpreted when the primary lens is longitudinal monitoring and model drift? This framing supports comparison while avoiding claims that cannot be established from bibliographic records alone.

The review follows a structured evidence-mapping protocol. First, the focal work defines the problem boundary. Second, nine adjacent publications are selected by controlled topical terms. Third, complete author sets are normalized and screened so that no two references in this manuscript share an author. Fourth, each item is assigned an explicit analytical role. This protocol makes the inclusion logic inspectable and prevents a long bibliography from masquerading as a coherent synthesis.

2. Evidence Map

Evidence node 2 is Ranjbar et al. (2022) [2], which addresses “Molecular insight into C60-grafted graphene oxide as a novel reverse osmosis membrane with low energy consumption for seawater desalination”. Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Evidence node 3 is Xu et al. (2020) [3], which addresses “Study on Antibacterial Properties of Cellulose Acetate Seawater Desalination Reverse-Osmosis Membrane with Graphene Oxide”. Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Evidence node 4 is Hussain et al. (2024) [4], which addresses “Modeling Approach to Estimate Energy Consumption of Reverse Osmosis and forward Osmosis Membrane Separation

Processes for Seawater Desalination”. Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Evidence node 5 is Wu et al. (2020) [5], which addresses “Recent development of graphene oxide based forward osmosis membrane for water treatment: A critical review”. Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Evidence node 6 is Safarpour et al. (2015) [6], which addresses “Thin film nanocomposite reverse osmosis membrane modified by reduced graphene oxide/TiO₂ with improved desalination performance”. Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Evidence node 7 is Choi et al. (2019) [7], which addresses “Membrane capacitive deionization-reverse electrodialysis hybrid system for improving energy efficiency of reverse osmosis seawater desalination”. Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Evidence node 8 is Kim et al. (2018) [8], which addresses “Non-swelling graphene oxide-polymer nanocomposite membrane for reverse osmosis desalination”. Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Evidence node 9 is Anqi et al. (2015) [9], which addresses “Numerical simulation of brackish water desalination by a reverse osmosis membrane”. Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Evidence node 10 is Raval et al. (2016) [10], which addresses “Direct fertigation with brackish water by a forward osmosis

system converting domestic reverse osmosis module into forward osmosis membrane element". Its controlled title terms place it directly within nanoscale desalination; in this review it is used to test how the focal argument behaves when viewed through longitudinal monitoring and model drift.

Taken together, references [1]-[10] form a compact, conflict-free map rather than a vote count. They span the focal contribution, adjacent methods, evaluation settings, and implementation considerations. Their value lies in triangulation: agreement can identify stable design assumptions, while differences reveal where metrics, datasets, populations, hardware, or operating conditions limit direct comparison.

3. Analytical Framework

The first analytical layer is construct alignment. A useful comparison requires that the outcome named in one study correspond to the outcome measured in another. For manuscript 01-P12-053, this means distinguishing nominally similar terms from operationally equivalent measures. The second layer is evidence strength. Peer-reviewed articles, conference papers, and preprints may all contribute, but their claims should be weighted by methodological transparency, sample or benchmark coverage, and the availability of uncertainty estimates.

The third layer concerns transfer. A result can be methodologically coherent yet fragile outside its original setting. Under the lens of longitudinal monitoring and model drift, transfer should be tested along at least four axes: data composition, task definition, resource envelope, and decision cost. The fourth layer is failure analysis. Aggregate performance alone cannot show whether errors concentrate in rare classes, difficult operating conditions, minority subgroups, boundary cases, or high-cost decisions. A credible research program therefore reports both central tendency and structured failure slices.

The fifth layer is reproducibility. At minimum, readers need a precise description of inputs, preprocessing, comparison baselines, evaluation metrics, and exclusion rules. Where code or data cannot be released, a procedural specification and sensitivity analysis can still make the work more auditable. This is especially important when the focal contribution is recent or when a formal venue record is still evolving.

4. Implications for Research and Practice

For researchers, the evidence map recommends designing experiments backward from the decision that the system or scientific claim is intended to support. That approach clarifies which baselines are meaningful, which uncertainty measures matter, and which ablations can attribute gains to specific components. It also discourages benchmark-only conclusions when the application depends on latency, reliability, calibration, manufacturing variation, environmental exposure, or human interpretation.

For practitioners, the key implication is staged adoption. A promising result should first be reproduced in a controlled environment, then stress-tested under shifted conditions, and finally monitored after deployment. Decision thresholds should reflect asymmetric costs rather than headline accuracy alone. Documentation should preserve data provenance, versioned configurations, and known failure conditions so that later changes can be traced.

5. Limitations and Research Agenda

This article is a structured evidence synthesis, not a new empirical trial. The adjacent works were selected for topical relevance and author independence; those criteria do not make their datasets or outcomes interchangeable. The next step is full-text extraction of study design, sample characteristics, effect estimates, uncertainty intervals, and implementation details. A preregistered comparison matrix would strengthen the analysis further.

Three questions follow. First, does the focal claim remain stable under alternative datasets or populations? Second, which component contributes most when cost and uncertainty are evaluated jointly? Third, what monitoring signal would reveal degradation early enough for intervention? Answering these questions would turn the present evidence map into a cumulative research program centered on longitudinal monitoring and model drift.

References

- Wang, T., Huang, L., Pei, J., Hu, X., & Jiang, H. (2022). Efficient water desalination using Bernoulli effect. *Desalination and Water Treatment*, 272, 37-49. <https://doi.org/10.5004/dwt.2022.28852>
- Ranjbar, T., Akbarzadeh, H., Mehrjouei, E., Abbaspour, M., Salemi, S., & Yaghoubi, H. (2022). Molecular insight into C60-grafted graphene oxide as a novel reverse osmosis membrane with low energy consumption for seawater desalination. *Desalination*, 542, 116062. <https://doi.org/10.1016/j.desal.2022.116062>
- Xu, P., & Na, N. (2020). Study on Antibacterial Properties of Cellulose Acetate Seawater Desalination Reverse-Osmosis Membrane with Graphene Oxide. *Journal of Coastal Research*, 105(sp1). <https://doi.org/10.2112/jcr-si105-052.1>
- Hussain, Y., Irfan, M., & Gul, S. (2024). Modeling Approach to Estimate Energy Consumption of Reverse Osmosis and forward Osmosis Membrane Separation Processes for Seawater Desalination. *CEMP* 2023, 17. <https://doi.org/10.3390/materproc2024017017>
- Wu, W., Shi, Y., Liu, G., Fan, X., & Yu, Y. (2020). Recent development of graphene oxide based forward osmosis membrane for water treatment: A critical review. *Desalination*, 491, 114452. <https://doi.org/10.1016/j.desal.2020.114452>
- Safarpour, M., Khataee, A., & Vatanpour, V. (2015). Thin film nanocomposite reverse osmosis membrane modified by reduced graphene oxide/TiO₂ with improved desalination performance. *Journal of Membrane Science*, 489, 43-54. <https://doi.org/10.1016/j.memsci.2015.04.010>
- Choi, J., Oh, Y., Chae, S., & Hong, S. (2019). Membrane capacitive deionization-reverse electrodialysis hybrid system for improving energy efficiency of reverse osmosis seawater desalination. *Desalination*, 462, 19-28. <https://doi.org/10.1016/j.desal.2019.04.003>
- Kim, S., Ou, R., Hu, Y., Li, X., Zhang, H., Simon, G.-P., & Wang, H. (2018). Non-swelling graphene oxide-polymer nanocomposite membrane for reverse osmosis desalination. *Journal of Membrane Science*, 562, 47-55. <https://doi.org/10.1016/j.memsci.2018.05.029>
- Anqi, A.-E., Alkhamis, N., & Oztekin, A. (2015). Numerical simulation of brackish water desalination by a reverse osmosis membrane. *Desalination*, 369, 156-164. <https://doi.org/10.1016/j.desal.2015.05.007>
- Raval, H.-D., & Koradiya, P. (2016). Direct fertigation with brackish water by a forward osmosis system converting domestic reverse osmosis module into forward osmosis membrane element. *Desalination and Water Treatment*, 57(34), 15740-15747. <https://doi.org/10.1080/19443994.2015.1075432>